



Quattro Pin SD Slim Slim Pin

8 CD 2.0 OSDP v.2

- Secure channel
- Configuration by protocol commands or by configuration card
- Durable and reliable access control reader armed with highest level Mifare® DESFire security
- Built-in OSDP v.2 support, enabling bi-directional reader-controller communication
- Extremely low power consumption – up to 60 % more energy-efficient
- Eco-sensitive construction
- Powerful, unique and customisable security features you choose and program yourself
- Open technology: no device supplier of technology dependencies
- Robust, reliable, flexible and utterly secure standalone capability
- Easy and convenient technology and security level migrations

Technical specifications

Operating Frequency	13,56Mhz
Voltage	+10 +30 VDC
Current Consumption	20 mA @ 24 VDC, max 60 mA
RFID chip support	MIFARE® DESFire Ev1: UID + Application files , MIFARE® Classic: UID + Sectors, MIFARE® Ultralight UID + Pages, MIFARE® Plus UID security levels 1 and 3, MIFARE® SmartMX (MIFARE® Classic emulation mode), NFC (UID), Mifare Classic 7 Byte UID + sectors. Mifare DESFire Ev2: UID+application files.
Keypad	2 x 6 Capacitive, 3 x 4 mechanical
Dimensions of housing (hwxwd)	Quattro Pin S: 85,1 x 85,1 x 24 mm, Slim, Slim Pin: 141 x 43 x 19 mm
Material of housing	Plastic
Installation method	Quattro: To a standard electrical socket with screws
Colour	Black
Customized versions	Yes, with sticker
Protection class	IP67: with the pigtail cable option, IP54: with the connector option
IK rating	Slim Pin: IK-09
Inflammatory class	Slim and Quattro housings: Horizontal specimen: UL94 HB, vertical specimen: UL94 V-2
Operational temperature range	-40 °C - +55 °C
Storage temperature range	-40 °C - +55 °C
I/O's	2 FET output, 1 General purpose input
RS-485	OSDP V2 (not compatible with OSDP V1)
EMC	Meets CE requirements
Field strength	According to EN300330
Encryption	AES or triple DES between card and reader, secure channel between reader and host
Cable	LIYY 3m, delivered only with pigtail reader
Connector option	Slim & Quattro (pigtail as a default)
LED	3 x Three-colour LED
Led control	By protocol
Buzzer	Yes
Buzzer control	By protocol
Optical Tamper	Yes
Keypad backlight control	By protocol

Eco 20 is a new generation of Idesco products. Eco 20 stands for less power consumption, improved connectivity with other products and smaller carbon footprint through sustainable manufacturing materials and methods. www.idesco.fi/eco20

Idesco Oy reserves the right to revise this publication and to make changes to its content as well as the right to change or discontinue these products, at any time, without obligation to notify any person or entity of such revisions or changes. All trademarks and registered trademarks are property of their respective owners. 28.2.2018. C00774E v.1.03.